



## V - REACTIVITY INFORMATION

STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE	CONDITIONS TO AVOID None
HAZARDOUS DECOMPOSITION PRODUCTS May liberate hydrogen gas	
HAZARDOUS POLYMERIZATION <input type="checkbox"/> MAY OCCUR <input checked="" type="checkbox"/> WILL NOT OCCUR	CONDITIONS TO AVOID None
INCOMPATIBILITY (MATERIALS TO AVOID) <input type="checkbox"/> WATER <input checked="" type="checkbox"/> OTHER    Hydrofluoric acid and strong alkalis	

### VI - SPILL OR LEAK PROCEDURE INFORMATION

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED If uncontaminated, collect substance with a vacuum. If contaminated, use appropriate collection methods in accordance with federal, state and local laws. Avoid creating excess dust.
WASTE DISPOSAL METHODS Normal disposal. Keep out of drains; may plug up drains and/or pipes

### VII - SPECIAL PROTECTION INFORMATION

VENTILATION TYPE	Local ventilation acceptable. If above TLV level, use mechanical vent
RESPIRATORY PROTECTION	NIOSH-approved respirator in dusty environment
PROTECTIVE GLOVES Rubber	EYE PROTECTION Use dust goggles
OTHER PROTECTIVE EQUIPMENT Long-sleeve shirt, full-length trousers, waterproof boots recommended	

### VIII - STORAGE AND HANDLING INFORMATION

STORAGE TEMPERATURE MAX.    N/A    MIN.    N/A	INDOOR N/A	HEATED N/A	REFRIGERATED N/A	OUTDOOR N/A
Take normal precautions against spillage of bulk material. Avoid creating respirable dust. Avoid storage in moist environment, as product may form into hard mass upon exposure to water or to any excessive moisture.				

### IX - TOXICITY INFORMATION

Prolonged exposure to silica dust above the threshold limit may cause scarring of the lungs, with a cough or shortness of breath. This product contains crystalline silica and traces of compounds of arsenic and lead, chemicals listed by the State of California (Prop. 65) as causing cancer or reproductive toxicity.
--

### X - MISCELLANEOUS INFORMATION

WARNING: Excessive inhalation of dust results in respiratory disease, including siliosis and pulmanory fibrosis. Avoid breathing or creating excessive dust. Warn workers of the possible hazards of breathing material. Use barrier creams to protect skin. The International Agency of Research (ARC) evaluated that there is "limited evidence" for the carcinogenicity of crystalline silica with respect to mumans. Advise and recommend workers to use appropriate protective equipment. Regarding the "1" toxicity rating, it should be noted that a worker exposed to the product for the majority of his working experience may develop more serious health concerns than the occasional user.
---

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF.

**SEDDON MIRA-MENT™ Patching Cement**