FIBERGLASS DIVISION

HOLE-FORMER/KNOCKOUT CYLINDRICAL WALL

LOW DRAFT or MINIMUM TAPER or BOOT STYLE


PARALLEL

131/8" OFFSET

ROUND

HOLE SIZE (DIAMETER)	48" i.d.	60" I.D.	72" I.D.	84" ı.d.	96" I.D.	120" I.D.	144" I.D.
7"	_	YES	_	_	YES	1	_
8"	_	YES	** YES	_	YES	_	_
9"	_	YES	YES	_	_	_	_
10"	_	YES	YES	_	YES	YES	_
11"	YES	YES	YES	_	YES	_	_
12"	_	**** YES	YES	YES	* YES	*** YES	YES
13"	_	YES	_	_	-	1	_
14"	_	_	YES	_	_	-	_
16"	_	YES	YES	_	YES	_	_


STANDARD WALL THICKNESS					
24" I.D. = 3"	84" I.D. = 8"				
36" I.D. = 4"	96" I.D. = 9"				
42" I.D. = 4½"	108" I.D. = 10"				
48" I.D. = 5"	120" I.D. = 12"				
60" I.D. = 6"	144" I.D. = 12"				
72" I.D. = 7"					




MOUNTING HARDWARE

MAGNETS
SLIDE BAR
NC THREAD INSERT
COIL INSERT (1/2" OR 3/4")
BOLT

<u>CPH</u> "cost per hole" is based on 500 uses, the <u>average</u> number of uses that customers get from a Blackthorn-manufactured fiberglass hole-former, derived from a customer survey. Your number of uses could be more than 500. Average number of uses may vary.





BLACKTHORN MANUFACTURES CUSTOM FIBERGLASS PRODUCTS. IF YOU NEED A SIZE NOT LISTED, CALL FOR A QUOTE.

800-836-6113

937-836-9296 • 836-9395 (FAX)



- 6113 BROOKVILLE SALEM ROAD ◆
 - CLAYTON OH 45315
- www.blackthorn-inc.com
- sales@blackthorn-inc.com