FIBERGLASS DIVISION

HOLE-FORMER/KNOCKOUT RECTANGULAR

CYLINDRIC	AL WALL				RECTA	NGULAR	
KNOC	KOUT			С	YLINDR	ICAL WAL	L
				T	HOLE SIZE	WALL X I.D.	Γ
HOLE SIZE	WALL x I.D.			Ē	32"w x 8" н	4" x 36"	1
22.5"w x 41.5"н	1.5" x 34"			Ī	30"w x 18" н	4" x 36"	
1.5" WALL X 34" KNOCK	KOUT			-	4" wa	ll x 36" I.D.	-
ATTACHES TO OU OF A 2.5FT MAR					HOLE SIZE	WALL x I.D.	
(LEAVES 2" OF			** NOTE **	Γ	26"w x 7"н	5" x 48"	7
HOLE SIZE	WALL x I.D.		NOTE		5" wal	ll x 48" I.D.	-
18"w x 18"н	3" x 52"	The	sizes listed are cur	rent			
24"w x 24"н	3" x 52"		mold sizes. Blackthorn can				
3" WALL X 52" I.D. (58" O.D.) KNOCKOUT ATTACHES TO OUTER JACKET OF A 4' MANHOLE MOLD (LEAVES 2" OF CONCRETE) DIACKTION Call modify/"block-out" these molds to create <u>any</u> part sizes that may fall between what is listed.							
	We can build-up (add 2	25%) OR cut-	down (add 10%) the wall of any FW part	to a non-sta	Indard wall thickness.		
ACKTHORN MANUFACTURES IF YOU NEED A SIZE NOT			TS.			_	



937-836-9296 🐵 836-9395 (гах)



₽

www.blackthorn-inc.com

sales@blackthorn-inc.com

6113 BROOKVILLE SALEM ROAD

CLAYTON OH 45315

STANDARD W	STANDARD WALL THICKNESS					
24" I.D. = 3"	84" I.D. = 8"					
36" I.D. = 4"	96" I.D. = 9"					
42" I.D. = 4½"	108" I.D. = 10"					
48" I.D. = 5"	120" I.D. = 11"					
60" I.D. = 6"	144" I.D. = 12"					
72" I.D. = 7"						

MOUNTING HARDWARE MAGNETS SLIDE BAR NC THREAD INSERT COIL INSERT (1/2" OR 3/4") BOLT