FIBERGLASS DIVISION


FLATWALL HOLE-FORMER STEPPED

| HOLE SIZE SMALLER DIAMETER stepped to LARGER DIAMETER (A stepped to B) | WALL THICKNESS |
|--|----------------|
| 9" dia. STEPPED TO 14" dia. (SMALL STEP 2") | UP TO 6" |
| 10" dia. STEPPED TO 16" dia. (SMALL STEP 3") | UP TO 11" |
| 12" dia. STEPPED TO 18" dia TWO CHOICES (SMALL STEP 2") or (SMALL STEP 4") | UP TO 16" |
| 12" dia. STEPPED TO 20" dia. (SMALL STEP 3") | UP TO 16" |
| 15" dia. STEPPED TO 20" dia. (SMALL STEP 3") | UP TO 12" |
| 15" dia. STEPPED TO 22" dia. (SMALL STEP 2") or (SMALL STEP 4") | UP TO 12" |
| 15" dia. STEPPED TO 24" dia. (SMALL STEP 3") | UP TO 16" |
| 16" dia. STEPPED TO 20" dia. (SMALL STEP 2") | UP TO 8" |
| 18" dia. STEPPED TO 24" dia TWO CHOICES (SMALL STEP 3") or (SMALL STEP 3") | UP TO 16" |
| 18" dia. STEPPED TO 26" dia TWO CHOICES (SMALL STEP 3") or (SMALL STEP 4") | UP TO 12" |
| 18" dia. STEPPED TO 28" dia. (SMALL STEP 3") | UP TO 16" |
| 21" dia. STEPPED TO 30" dia. (SMALL STEP 3") | UP TO 16" |
| 24" dia. STEPPED TO 34" dia. (SMALL STEP 3") | UP TO 16" |
| 27" dia. STEPPED TO 34" dia. (SMALL STEP 4") | UP TO 12" |
| 30" dia. STEPPED TO 40" dia. (SMALL STEP 3") | UP TO 16" |
| 30" dia. STEPPED TO 42" dia. (SMALL STEP 3") | UP TO 16" |
| 36" dia. STEPPED TO 48" dia. (SMALL STEP 3") | UP TO 12" |
| 42" dia. STEPPED TO 54" dia. (SMALL STEP 4") | UP TO 12" |
| 48" dia. STEPPED TO 62" dia. (SMALL STEP 4") | UP TO 12" |



CLOSED BACKS AVAILABLE

ALL PARTS ARE BRACED to assist in their removal.



NOTE: We also have a <u>FSE-11-36</u>. This is a flatwall stepped hole-former for elliptical pipe. Step dimensions = 29" x 45" x 3" step stepped to 40.75" x 57.5" x 8" step



BLACKTHORN MANUFACTURES *CUSTOM FIBERGLASS PRODUCTS.*IF YOU NEED A SIZE NOT LISTED, CALL FOR A QUOTE.

800-836-6113

937-836-9296 * sales@blackthorn-inc.com

BLACKTHORN

- 6113 BROOKVILLE SALEM ROAD CLAYTON OH 45315
- www.blackthorn-inc.comsales@blackthorn-inc.com

MOUNTING HARDWARE

MAGNETS

MAGNETS
SLIDE BAR
NC THREAD INSERT
COIL INSERT (1/2" OR 3/4")
BOLT

NOTE: Stepped hole-formers are inherently difficult to strip out during their removal. Concrete should be thoroughly cured before attempting to remove the hole-former. Patience and care are required. Length of service may be less than a standard, non-stepped hole-former.